



# CHAPA PERFORADA AGUJEROS REDONDOS NORMALIZADOS


1 mm. Ø




1,20 mm. Ø




1,50 mm. Ø




2 mm. Ø




2,50 mm. Ø




3 mm. Ø




3,5 mm. Ø




4 mm. Ø




5 mm. Ø



6 mm. Ø



7 mm. Ø



8 mm. Ø




Diámetro	Distancia centros	Grueso en mm.	Coefficiente perforación
1	2	0,5 a 0,8	23
1,2	2,3	0,5 a 1	24
1,5	3	0,5 a 1	23
1,8	3	0,5 a 1	32
2	3,6	0,5 a 1,5	28
2,5	4	0,5 a 2	35
3	5	0,5 a	34

Diámetro	Distancia centros	Grueso en mm.	Coefficiente perforación
3,5	5,5	0,5 a 2,5	36
4	5	0,5 a 3	40
5	7,2	0,5 a 3	43
6	8,5	0,5 a 3	45
7	10	0,5 a 3	44
8	11,3	0,5 a 3	45


Previa consulta y bajo pedido, sujeto a cantidades mínimas de fabricación y a plazos de entrega convenidos, pueden suministrarse otros diámetros (entre 0,5 y 1) y otros espesores (entre 5 y 10 mm.)

# CHAPA PERFORADA AGUJEROS REDONDOS NORMALIZADOS


9 mm. Ø




10 mm. Ø




11 mm. Ø




12 mm. Ø




13 mm. Ø




14 mm. Ø




15 mm. Ø




16 mm. Ø



18 mm. Ø




20 mm. Ø



25 mm. Ø



30 mm. Ø



Diámetro	Distancia centros	Grueso en mm.	Coefficiente perforación
9	13	0,5 a 3	43
10	14	0,5 a 3	46
11	15,2	0,5 a 3	47
12	16	0,5 a 3	51
13	17	0,5 a 3	53
14	19	0,5 a 3	49
15	19	0,5 a 3	56
16	20	0,5 a 3	58

Diámetro	Distancia centros	Grueso en mm.	Coefficiente perforación
17	23,5	0,5 a 3	47
18	23	0,5 a 3	55
19	24	0,5 a 3	56
20	25,2	0,5 a 3	57
22	29	0,5 a 3	52
25	32	0,5 a 3	55
28	35	0,5 a 5	58
30	37	0,5 a 3	59